

LARUE

Detachable snowblower



D55



Detachable snowblower

Performance¹

Capacity: up to 2,750 tons/hour
Casting distance: up to 46 m (150 ft.)

Dimensions²

Length from attach plate to front: 2,083 mm (82 in.)
Overall width: 2,795 - 2,895 mm (110 - 114 in.)
Overall height³: 3,530 - 3,988 mm (139 - 157 in.)
Working height: 1,473 mm (58 in.)
Weight²: 4,082 kg (9,000 lb)

Engine

Various makes
Power: from 186 kW (250 hp) to 205 kW (275 hp)

Driveline system

Mechanical type equipped with clutch and protecting devices

Hydraulic system

Pump: direct drive
Filter with replaceable cartridge
Valves electro-hydraulic type
Controlled by in-cab multifunctional joystick

Impeller

Easy replaceable blades
Heavy duty spoke type
Impeller casing made of steel (highly abrasive resistant)
Hydraulic impeller casing rotation

Conveyor

Type: ribbon (serrated)
Diameter: 914 mm (36 in.)

Truck loading chute

Hydraulically controlled
Horizontal rotation angle: 300°
Casting distance: 1.2 m (4 ft.) to 15 m (50 ft.)
Telescopic section of 472 mm (18 in.) (optional)

Options

Engine: 224 kW (300hp)
Female quick attach
Hydraulic steering vanes
Impeller casing having a 140° adjustable cast angle: flat from the right to 40° to the left
Carbide type: impeller casing, loading chute, scraper blade and/or skates
Residential type muffler
High resistance rubber scraper blade
Battery charger and/or battery heater
Trumpet horn
Telescopic loading chute

Notes:

1. Theoretical and depends on snow conditions.
2. Varies with options, measured without fuel.
3. With telescopic truck loading chute option.

Due to continuous improvement, the specifications in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or your local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.**
660, Lenoir, Québec (Québec) Canada G1X 3W3
Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799
Web site: **www.jalarue.com** | E-mail: **jalarue@jalarue.com**

Your authorized distributor:

