

LARUE

Detachable snowblower



D60



Detachable snowblower

Performance¹

Capacity: up to 3,000 tons/hour
Casting distance: up to 46 m (150 ft.)

Dimensions

Length from attach plate to front: 2,006 mm (79 in.)
Overall length: 2,590 mm (102 in.)
Overall width: 2,800 - 2,900 mm (110 - 114 in.)
Overall height²: 3,530 - 3,990 mm (139 - 157 in.)
Working height: 1,524 mm (60 in.)
Weight³: 5,397 kg (11,900 lb)
Wheel loader range: 2.50 - 3.50 cu. yd.

Engine

Power: 224-298 kW (300-400 hp) at 2,200 RPM

Driveline system

Mechanical type equipped with clutch and protecting devices

Hydraulic system

Pump: direct drive
Filter with replaceable cartridge
Valves electro-hydraulic type
Controlled by in-cab multifunctional joystick

Impeller

Diameter: 1,016 mm (40 in.)
Easy replaceable blades
Heavy duty spoke type
Impeller casing made of steel (highly abrasive resistant)
Hydraulic impeller casing rotation

Conveyor

Diameter: 660 mm (26 in.)
Two heavy duty augers
Ice-cutting teeth

Truck loading chute

Hydraulically controlled
Horizontal rotation angle: 300°
Casting distance: 1.2 m (4 ft.) to 15 m (50 ft.)
Telescopic section of 472 mm (18 in.) (optional)

Options

Female quick attach
Hydraulic steering vanes
Impeller casing having a 140° adjustable cast angle:
Flat from the right to 40° to the left.
Carbide type: impeller casing, loading chute, scraper blade and/or skates
Residential type muffler
High resistance rubber scraper blade
Replaceable conveyor ice cutting teeth
Battery charger and/or battery heater
Trumpet horn
Telescopic loading chute

Notes:

1. Theoretical and depends on snow conditions.
2. With telescopic truck loading chute option.
3. Varies with options, measured without fuel.



Due to continuous improvement, the specifications in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or our local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.**
660, Lenoir, Québec (Québec) Canada G1X 3W3
Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799
Web site: www.jalarue.com | E-mail: jalarue@jalarue.com

Your authorized distributor: