

# LARUE

## Detachable snowblower



# D65



## Detachable snowblower

### Performance<sup>1</sup>

Capacity: up to 2,800 tons/hour  
Casting distance: up to 46 m (150 ft.)

### Dimensions<sup>2</sup>

Length from attach plate to front: 2,184 mm (86 in.)  
Overall width: 2,795 - 2,895 mm (110 - 114 in.)  
Overall height: 3,530 - 3,988 mm (139 - 157 in.)  
Working height<sup>3</sup> 1,486 mm (58.5 in.)  
Weight<sup>2</sup>: 5,397 kg (11 900 Lb)

### Engine

Various makes  
Power: from 224kW (300 hp) to 298kW (400 hp)

### Driveline system

Transmission: mechanical drive with maintenance free clutch 3 discs, roller chain reduction, fully enclosed in oil bath, 2 spiral bevel gear box, 2 planetary gear reduction

### Hydraulic system

Pump: direct drive  
Filter with replaceable cartridge  
Valves electro-hydraulic type  
Controlled by in-cab multifunctional joystick

### Impeller

Easy replaceable blades  
Heavy duty spoke type  
Impeller casing made of steel (highly abrasive resistant)  
Hydraulic impeller casing rotation

### Conveyor

Type: ribbon (serrated)  
Diameter: 1,016 mm (40 in.)

### Truck loading chute

Hydraulically controlled  
Horizontal rotation angle: 300°  
Casting distance: 1.2 m (4 ft.) to 15 m (50 ft.)  
Telescopic section of 472 mm (18 in.) (optional)

Due to continuous improvement, the specifications in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or your local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.**  
660, Lenoir, Québec (Québec) Canada G1X 3W3  
Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799  
Web site: [www.jalarue.com](http://www.jalarue.com) | E-mail: [jalarue@jalarue.com](mailto:jalarue@jalarue.com)

### Options

Female quick attach  
Hydraulic steering vanes  
Impeller casing having a 140° adjustable cast angle: flat from the right to 40° to the left  
Carbide type: impeller casing, loading chute, scraper blade and/or skates  
Residential type muffler  
High resistance rubber scraper blade  
Battery charger and/or battery heater  
Trumpet horn  
Telescopic loading chute

### Notes:

1. Theoretical and depends on snow conditions.
2. With CAT C-9 engine, no attachment and no fuel. Varies with options.
3. With telescopic truck loading chute option



**Your authorized distributor:**