

# LARUE

## Single stage Detachable snowblower



# D77





## Single stage Detachable snowblower

### Performance<sup>1</sup>

Capacity: from 4,500 to 5,000 tons/hour  
Casting distance: up to 55 m (180 ft.)

### Dimensions

Length from attach plate to front:  
3,276 mm (129 in.)  
Overall width: 2,920 mm (115 in.)  
Working height: 1,905 mm (75 in.)  
Weight<sup>2</sup>: 7,258 kg (16,000 lb)  
Wheel loader range: 3.50 - 4.50 cu. yd.

### Engine

Power: 388 kW (520 hp)

### Driveline system

Mechanical type equipped with clutch  
and protecting devices.

### Hydraulic system

Pump: direct drive  
Filter with replaceable cartridge  
Valves electro-hydraulic  
Controlled by in-cab multifunctional joystick

### Impeller

Impeller casting having a 90° adjustable cast angle:  
flat from the right to vertical at 90° to the left  
Diameter: 1,778 mm (70 in.)  
Impeller blades: 6

### Impeller casing

One piece shotgun type

### Options

Engine: 444 kW (595 hp)  
Female quick attach  
Hydraulic steering vanes  
Residential type muffler

### Notes:

1. Theoretical and depends on snow conditions.
2. With Cat C13 engine, no attachment and no fuel, varies with options.



Due to continuous improvement, the specifications in this brochure may change without prior notice.

For more information, please contact the manufacturer J.A. Larue Inc. or your local distributor.

Deposit brand 1999, all right reserved | Manufactured by: **J.A. Larue Inc.**  
660, Lenoir, Québec (Québec) Canada G1X 3W3  
Tel: **418-658-3003** | Toll free: 1-877-658-3013 | Fax: 418-658-6799  
Web site: **www.jalarue.com** | E-mail: **jalarue@jalarue.com**

**Your authorized distributor:**